



COMPRESOR DE ACOPLAMIENTO DIRECTO

- > De 35 a 50 CV (26 a 37 kw)
- > Nuevo elemento C80
- > **Transmisión Directa**
- > Control total del equipo mediante microprocesador ES4000



DRB 40 VF DRY

DRB sin Secador															
Código	Modelo	Elemento	bar	HP	KW	l/min	Secador	dB	Volt.	ancho	largo	alto	Kg	€	
DRB - VELOCIDAD FIJA															
4152 0180 98	DRB35 - 7,5 CE	C80	7,5	35	26	4500	-	69	400/3/50	780	1350	1580	444	16.500	
4152 0180 99	DRB35 - 8,5 CE	C80	8,5	35	26	4320	-	69	400/3/50	780	1350	1580	444	16.500	
4152 0181 00	DRB35 - 10 CE	C80	10	35	26	3960	-	69	400/3/50	780	1350	1580	444	16.500	
4152 0181 01	DRB35 - 13 CE	C80	13	35	26	3420	-	69	400/3/50	780	1350	1580	444	16.500	
4152 0181 02	DRB40 - 7,5 CE	C80	7,5	40	30	5460	-	70	400/3/50	780	1350	1580	492	22.000	
4152 0181 03	DRB40 - 8,5 CE	C80	8,5	40	30	4980	-	70	400/3/50	780	1350	1580	492	22.000	
4152 0181 04	DRB40 - 10 CE	C80	10	40	30	4560	-	70	400/3/50	780	1350	1580	492	22.000	
4152 0181 05	DRB40 - 13 CE	C80	13	40	30	4020	-	70	400/3/50	780	1350	1580	492	22.000	
4152 0181 06	DRB50 - 7,5 CE	C80	7,5	50	37	6120	-	71	400/3/50	780	1350	1580	514	23.500	
4152 0181 07	DRB50 - 8,5 CE	C80	8,5	50	37	5640	-	71	400/3/50	780	1350	1580	514	23.500	
4152 0181 08	DRB50 - 10 CE	C80	10	50	37	5040	-	71	400/3/50	780	1350	1580	514	23.500	
4152 0181 09	DRB50 - 13 CE	C80	13	50	37	4560	-	71	400/3/50	780	1350	1580	514	23.500	
DRB - VELOCIDAD VARIABLE															
4152 0181 10	DRB35 VF 12,5 CE	C80	5,5-12,5	35	26	780-4860	-	69	400/3/50	780	1350	1580	444	21.000	
4152 0181 11	DRB40 VF 12,5 CE	C80	5,5-12,5	40	30	1020-5820	-	70	400/3/50	780	1350	1580	492	29.000	
4152 0181 12	DRB50 VF 12,5 CE	C80	5,5-12,5	50	37	1020-6360	-	71	400/3/50	780	1350	1580	514	30.500	
DRB con Secador															
Código	Modelo	Elemento	bar	HP	KW	l/min	Secador	dB	Volt.	ancho	largo	alto	Kg	€	
DRB - VELOCIDAD FIJA															
4152 0181 25	DRB35 - DRY 7,5 CE	C80	7,5	35	26	4500	SI	69	400/3/50	780	1350	1580	513	20.500	
4152 0181 26	DRB35 - DRY 8,5 CE	C80	8,5	35	26	4320	SI	69	400/3/50	780	1350	1580	513	20.500	
4152 0181 27	DRB35 - DRY 10 CE	C80	10	35	26	3960	SI	69	400/3/50	780	1350	1580	513	20.500	
4152 0181 28	DRB35 - DRY 13 CE	C80	13	35	26	3420	SI	69	400/3/50	780	1350	1580	513	20.500	
4152 0181 29	DRB40 - DRY 7,5 CE	C80	7,5	40	30	5460	SI	70	400/3/50	780	1350	1580	607	25.500	
4152 0181 30	DRB40 - DRY 8,5 CE	C80	8,5	40	30	4980	SI	70	400/3/50	780	1350	1580	607	25.500	
4152 0181 31	DRB40 - DRY 10 CE	C80	10	40	30	4560	SI	70	400/3/50	780	1350	1580	607	25.500	
4152 0181 32	DRB40 - DRY 13 CE	C80	13	40	30	4020	SI	70	400/3/50	780	1350	1580	607	25.500	
4152 0181 33	DRB50 - DRY 7,5 CE	C80	7,5	50	37	6120	SI	71	400/3/50	780	1350	1580	629	27.000	
4152 0181 34	DRB50 - DRY 8,5 CE	C80	8,5	50	37	5640	SI	71	400/3/50	780	1350	1580	629	27.000	
4152 0181 35	DRB50 - DRY 10 CE	C80	10	50	37	5040	SI	71	400/3/50	780	1350	1580	629	27.000	
4152 0181 36	DRB50 - DRY 13 CE	C80	13	50	37	4560	SI	71	400/3/50	780	1350	1580	629	27.000	
DRB - VELOCIDAD VARIABLE															
4152 0181 37	DRB35 VF DRY 12,5 CE	C80	5,5-12,5	35	26	780-4860	SI	69	400/3/50	780	1830	1580	513	25.000	
4152 0181 38	DRB40 VF DRY 12,5 CE	C80	5,5-12,5	40	30	1020-5820	SI	70	400/3/50	780	1830	1580	607	32.500	
4152 0181 39	DRB50 VF DRY 12,5 CE	C80	5,5-12,5	50	37	1020-6360	SI	71	400/3/50	780	1830	1580	629	35.000	

Caudal de aire medido según la norma ISO 1217 ed. 4 2009. Nivel de ruido medido según la norma ISO 2151: 2004 mediante ISO 9614/2. Disponible en tensiones especiales (consultar).