



GAMA PKM

BASE / BASE SOBRE DEPÓSITO / BASE SOBRE DEPÓSITO CON SECADOR

- › De 7,5 a 20 CV
- › Nuevo Elemento C55*
- › Tarjeta ES4000 Basic



NUEVA TARJETA
ES4000 Basic



Base PKM																
Código	Modelo	Elemento	L	bar	HP	KW	l/min	Secador	Filtros	dB	Volt.	ancho	largo	alto	Kg	€
4152 0213 11	PKM 7.5/10 400/50 FM CE	C55*	-	10	7,5	5,5	696	-	-	64	400/3/50	720	850	980	160	7.000
4152 0213 13	PKM 10/10 400/50 FM CE	C55*	-	10	10	7,5	996	-	-	65	400/3/50	720	850	980	170	7.500
4152 0213 16	PKM 15/10 400/50 FM CE	C55*	-	10	15	11	1416	-	-	69	400/3/50	720	850	980	185	7.900
4152 0213 19	PKM 20/10 400/50 FM CE	C55*	-	10	20	15	1680	-	-	71	400/3/50	720	850	980	200	8.500

PKM sobre Depósito																
Código	Modelo	Elemento	L	bar	HP	KW	l/min	Secador	Filtros	dB	Volt.	ancho	largo	alto	Kg	€
4152 0213 55	PKM 7.5/10 400/50 TM500 CE	C55*	500	10	7,5	5,5	696	-	-	64	400/3/50	720	1945	1468	257	7.900
4152 0213 57	PKM 10/10 400/50 TM500 CE	C55*	500	10	10	7,5	996	-	-	65	400/3/50	720	1945	1468	267	8.300
4152 0213 60	PKM 15/10 400/50 TM500 CE	C55*	500	10	15	11	1416	-	-	69	400/3/50	720	1945	1468	282	8.900
4152 0213 63	PKM 20/10 400/50 TM500 CE	C55*	500	10	20	15	1680	-	-	71	400/3/50	720	1945	1468	297	9.400

PKM sobre Depósito + Secador																
Código	Modelo	Elemento	L	bar	HP	KW	l/min	Secador	Filtros	dB	Volt.	ancho	largo	alto	Kg	€
4152 0213 66	PKM 7.5S/10 400/50 TM500 CE	C55*	500	10	7,5	5,5	696	SI	-	64	400/3/50	720	1945	1468	292	9.400
4152 0213 68	PKM 10S/10 400/50 TM500 CE	C55*	500	10	10	7,5	996	SI	-	65	400/3/50	720	1945	1468	300	9.800
4152 0213 71	PKM 15S/10 400/50 TM500 CE	C55*	500	10	15	11	1416	SI	-	69	400/3/50	720	1945	1468	315	10.400
4152 0213 74	PKM 20S/10 400/50 TM500 CE	C55*	500	10	20	15	1680	SI	-	71	400/3/50	720	1945	1468	330	10.800

PKM sobre Depósito + Secador + Filtros																
Código	Modelo	Elemento	L	bar	HP	KW	l/min	Secador	Filtros	dB	Volt.	ancho	largo	alto	Kg	€
4152 0213 77	PKM 7.5S/10 400/50 TM500F CE	C55*	500	10	7,5	5,5	696	SI	SI	64	400/3/50	720	1945	1468	297	9.900
4152 0213 79	PKM 10S/10 400/50 TM500F CE	C55*	500	10	10	7,5	996	SI	SI	65	400/3/50	720	1945	1468	305	10.400
4152 0213 82	PKM 15S/10 400/50 TM500F CE	C55*	500	10	15	11	1416	SI	SI	69	400/3/50	720	1945	1468	320	10.900
4152 0213 85	PKM 20S/10 400/50 TM500F CE	C55*	500	10	20	15	1680	SI	SI	71	400/3/50	720	1945	1468	335	11.400

Cuadro arrancador estrella-triángulo incluido en todos los modelos. Caudales según norma ISO 1217 apartado C y Cagi-Pneurop PN2 CPTC2. Disponibles a 60 Hz y tensiones especiales. Disponibles a 8 bar en todas las potencias. Disponibles a 13 bar en 10-15-20 CV.